

PAVERCOAT 43

Concrete Pavement Coating

DESCRIPTION

PAVERCOAT 43 is a two part, advanced waterborne epoxy-modified acrylic coating for use outdoor as well as indoor. PAVERCOAT 43 is ideal for use in repair and maintenance of stamped concrete installations by providing a strong adhering layer that has exceptional abrasion resistance and long-term durability.

PAVERCOAT 43 is combined with Colorants to offer a wide range of colors.

SURFACE PREPARATION

PAVERCOAT 43 System can be applied to either an asphalt or concrete base. Its versatility is coupled with strong adhesion and superb anti slip finish.

Dirt, debris, water and contaminants if present on the surface will affect adhesion. Thoroughly clean surface using a broom and backpack blower or, in severe situations, use a power washer. Areas containing chemical contaminants such as vehicle fluids need to be treated using a degreasing solution. Proper removal of contaminants and degreasing solution is necessary prior to coating application. Care should be taken to ensure that the substrate is dry before applying the coating. An environmentally friendly cleaner should be used.

PRIMING

Adhesion promoter may be used for polished asphalt. Concrete applications will require a 30% water diluted mix PRIMER. No precipitation should be expected within 24 hours.

RECOMMENDED APPLICATION

PAVERCOAT 43 may be applied over old and patched stamped or smooth concrete installations in thin coats by brush, roller or textured sprayer. Typical pedestrian applications require 2 layers of coating. Vehicle applications may require 3 layers or more depending on the condition of the floor.

HIGHLIGHTING

Following PAVERCOAT 43 installation and after a drying period depending on prevailing temperatures, a proper highlighting coating may be applied in a complimentary or contrasting color to provide a realistic 3D look.

PACKAGE

One kit of PAVERCOAT 43 consists of:
23,5 Kg pail of Part A
1,5 Kg of Part B

APPLICATION COVERAGE

Application Coverage Rates

COVERAGE (approx.)		THICKNESS(Approx)	
Layers	Sqm/25 kg	WET mm	DRY mm
3	18	0,8	0,44
4	14	1,1	0,62

MAINTENANCE GUIDELINES

PAVERCOAT 43 system is an all-weather surface coating and requires minimal maintenance. The surface should be cleared of all dirt or leaves using a brush. The surface should be cleaned with mild detergents and may be pressure washed with a power washer.