

TOPCRETE 300

COLORED RELEASE AGENT

DESCRIPTION:

PaveCrete 300 is a specially formulated powder, water repellent, designed to ensure that the finest details of texturing mats are transferred accurately to freshly placed concrete.

Uses:

As a dry-shake on freshly poured concrete, colored or grey to aid finishing by preventing fresh concrete from adhering to stamping tools, and to create a distinct color to the concrete in the form of antique or rustic color. This effect of color can be made on colored or un-colored concrete surfaces and with or without the use of stamping tools.

ADVANTAGES:

- Water repellent and thus prevents fresh concrete from sticking to stamping tools.
- Creates antique color impressions when applied to fresh concrete surface.
- Available in many colors to either match or contrast with the color of concrete being placed.

APPLICATION:

Before applying PaveCrete 300 protect all surfaces where color is not desired, or to keep the surrounding areas clean as it will be very hard to clean and remove from other finished works. All concrete finishers and all near-by personnel must wear dust masks while applying PaveCrete 300 or removing the excess of it during the final stage. PaveCrete 300 may be applied to the surface of the freshly placed concrete

as soon as all standing water has disappeared from the concrete surface or after finishing the concrete surface treatment with PaveCrete 200 and while the concrete is still in the plastic condition. Typically, concrete should receive at least a (fresno) finish. If PaveCrete 200 has been applied, the finishing would be more extensive.

Apply PaveCrete 300 in broadcasting fashion until a thin uniform layer covers the concrete surface. Avoid applying PaveCrete 300 when it is windy. PaveCrete 300 should be removed from the concrete surface when removal can be safely accomplished without any damage to the cured concrete surface. Excess PaveCrete 300 should be swept off the slab using soft bristle broom or vacuum cleaner. Residual PaveCrete 300 may be left for an antique effect or removed to the degree desired using a high pressure washer or by a diluted acid wash.

The amount of PaveCrete 300 adhering to the concrete surface will depend upon how hard the concrete surface was at the time of application, the method and degree of cleaning. A softer concrete surface will retain more PaveCrete 300 than a harder concrete surface, and an acid wash will remove more PaveCrete 300 than water jet cleaning.

PACKAGING:

15 KG. Plastic Pail.

Manufactured by TEKNO In Turkey

TopCrete International S.A.R.L. Galaxy Center – Blvd. Camille Chamoun, Chiyah

Beirut – Lebanon Tel: (9611) 544111 Fax: (9611) 546663 GSM: (9613) 882210 E-mail : info@topcrete.com

WEB: www.topcrete.com